Urban Forest Appendix Details For Section M – Development Manual Tree Planting & Establishment Best Management Practices

Inspection Certificate					
UF.1.1	JF.1.1 Initial Acceptance Certificate – Tree Planting and Soil Habitat Zone				
Soils					
UF.3.1	Soil Habitat Zone & Volume Requirements For Trees In Boulevards				
UF.3.2	Soil Habitat Zone & Root Pathways - Type 1 (Big O Pipe)				
UF.3.3	Soil Habitat Zone & Root Pathways - Type 2 (Silva Cells)				
UF.3.4	Soil Habitat Zone Installation & Specifications				
UF.3.5	Soil Habitat Zone & Silva Cells				
UF.3.6	Soil Volume Calculator (available from City of Kitchener Operations Division upon request)				
Tree Planting & Establishment					
UF.4.1	Standard Deciduous Tree Planting Detail				

Infrastructure Services Department





Initial Acceptance Certificate – Tree Planting and Soil Habitat


Dat	e of Inspection:	Subdivision #:	30T				
Sub	division Name:	Stage #:	58M				
Sub	divider :	Registered Plan #:					
Insp	pection Area (street, lot number etc.): _						
_	ification of Site Conditions as per Devo	nent Manual and Approved Stree	t Tree Planting Plan				
	Boulevard soil habitat constructed to	·					
	Front yard soil habitat topsoil depth						
		ther (specify depth of topsoil)	mm (min 450mm)				
	Front yard soil habitat scarified to 900mm depth						
	Street tree installation						
Con	nments:						
	rmation						
	I have inspected the site in accordance that the elements inspected are consand Approved Street Tree Planting Pl	ed in accordance with the City of	f Kitchener Subdivision Manual				
Cons	sultant (Name)	Consulting Firm					
Signa	ature	Date					
cc:	City of Kitchener, Engineering						

City of Kitchener Development Manual – April 2015

City of Kitchener, Operations









Note: A minimum of three root pathways will be accepted for small stature trees under special circumstances.





SECTION

Scale 1:100





Notes: If Granular 'A' exceeds 150mm depth - excess will be removed in the root pathway area and replaced with parent material.


A minimum of five root pathways required for large and medium stature trees, while three root pathways will be accepted for small stature trees under special circumstances.




Plotted by: yvonnew Filename: S:\Secured\Design & Development\5 - AutoCAD Library\4 - Details\900 - Plonting\UF.3.2 - ROOT PATHWAYS - TYPE 1.dwg










Subgrade Preparation

- 1. Scarify (subgrade) parent material with a toothed blade to a depth of 100mm where there are no underground utilities.
- 2. Where drain lines are identified slope the subgrade to the drain.
- 3. Drain lines if required.
- 4. Slopes adjacent to infrastructure are to be 1:1.



SUBGRADE PREPARATION (Adapted from Up By Roots, James Urban, 2008)

Scale 1:50




Soil Installation


- 1. 300 mm soil lifts
- 2. Lifts to be compacted to 80% standard proctor density.
- 3. Compost added to top lift (A Horizon) if specified.



SOIL INSTALLATION (Adapted from Up By Roots, James Urban, 2008)


Scale 1:50






Scale 1:200

Note: The location, size and design of the passive irrigation system, and soil testing/line inspection port shall be determined by the Project Designer and Irrigation Consultant, and approved by Operations. All Irrigation systems will be approved by Operations staff and will be consistent with current City of Kitchener Operations standards.



SECTION

This detail has been provided by Deep Root, with minor modifications. All Silva Cell designs will be reviewed and approved by Deep Root and City of Kitchener Operations staff.



TREE MUST BE STRAIGHT IN HOLE WITHOUT ANY SUPPORT

TREE TRUNK AND BRANCHES WILL NOT BE DAMAGED DURING TRANSPORT OR PLANTING AND WILL BE FREE OF WOUNDS AT TIME OF INSPECTION

PRUNE TO REMOVE BROKEN AND/OR INTERFERING BRANCHES ONLY. DO NOT PRUNE LEADER. REMOVE ALL NURSERY TABS/TIES, ETC.

TIES SHALL BE GREEN ARBORTIE, OR APPROVED EQUIVALENT. TIES SHALL FORM A LOOSE LOOP AROUND THE STAKE AND LOOP IN A FIGURE '8' AROUND THE TRUNK OF THE TREE. SECURE ARBORTIE TO THE STAKE USING 1" GALVANIZED ROOFING NAILS (SEE FOLLOWING SHEET FOR DETAIL).

2x2 WOODEN STAKES WITH FLEXIBLE TIES, PERMITTING TREE TO MOVE.

EXPANDABLE PROTECTIVE TREE GUARD 200mm HIGH

STRUCTURAL ROOTS WILL BE JUST BELOW SURFACE (2.5–7.5CM); ROOT FLARE MAY NOT BE VISIBLE ON YOUNG TREES. SEE STRUCTURAL ROOT DEPTH DETAIL.

50mm ORGANIC MULCH OR SHREDDED BARK. DO NOT MOUND AT BASE OF TRUNK. MULCH TAPERED TO GROUND LEVEL AT TRUNK.

100mm X 150mm WIDE SOIL RING

450mm (18") TO 900mm (36") SOIL DEPTH TREE PLANTING PER APPROVED TREE PLANTING PLAN.


BREAKUP COMPACTED SOIL FROM HOLE AND BACKFILL IN 150mm LIFTS. TAMP TO PREVENT SETTLEMENT.

REMOVE BURLAP AND TWINE FROM TOP 1/3 OF ROOT BALL. CUT TOP HORIZONTAL WIRE OF WIRE BASKET IN FOUR PLACES AND FOLD DOWN INTO PLANTING SOIL UNLESS BASKET IS A LOW PROFILE.

WIDTH OF TOP OF PLANTING HOLE WILL BE AT LEAST 1.5 TIMES ROOTBALL DIAMETER.

PLACE ROOTBALL ON UNDISTURBED SOIL, IF HOLE IS DUG TO DEEP COMPACT SOIL UNDER TO MAINTAIN REQUIRED DEPTH OF STRUCTURAL ROOTS. COMPACT SOIL.





STRUCTURAL ROOT DEPTH

Depth of roots at planting time is critical. It cannot be assumed that structural roots will be near the top of B&B stock. All B&B or tree container stock is to be planted so that the uppermost structural roots are within 2.5 to 7.5 cm when measured 10 cm from the trunk. The location of structural roots will be determined prior to the excavation of any tree planting holes are dug to ensure that the proper depth of the planting hole is achieved. Once planted any excess soil will be removed to meet the above standard. If the removal of the soil would result in an unstable root ball the tree is not be planted and there will be no charge to the City for its replacement. At no time is this process to result in the exposure of the structural roots, and or the root ball being planted too high.


 $Plotted \ by: \ yvonnew \qquad Filename: \ S:\ Secured\ besign \ \& \ Development\ 5 \ - \ AutoCAD \ Library\ 4 \ - \ Details\ 900 \ - \ Planting\ VF.4.1 \ - \ STREET \ TREE-PLANTING.dwg$




SCALE: N.T.S.

STANDARD TREE PLANTING FOR DECIDUOUS & CONIFEROUS TREES

OTANDARD TREET EARTING FOR DEGIDOOGG & GOMIL ERGOG TREES							
DESIGN	LAST REVISED	SCALE	DWG No.				
N/A		N.T.S.	111544				
DRAWN	PLOT DATE	FILE NAME	─── │ UF.4.1				
M. PARRIS	May 25, 2012						





C TREE TRUNK TIE DETAIL SCALE: N.T.S.

TREE PLANTING - SLOPE DETAIL SCALE: N.T.S.

TREE PLANTING DETAILS

- 1. DAMAGED TREES, TREES WITH POOR FORM OR ROOT STRUCTURE AND TREES NOT MEETING THE CANADIAN STANDARDS FOR NURSERY STOCK WILL BE REFUSED. THE CONTRACTOR IS ALSO RESPONSIBLE TO ENSURE THAT ALL PLANT MATERIAL, INCLUDING CULTIVARS AND TREE SIZES ARE PROVIDED AND INSTALLED AS STATED ON THIS PLAN. NO ALTERNATIVES, INCLUDING SPECIES, TREE SIZE WILL BE ACCEPTED UNLESS APPROVED BY THE COMMUNITY SERVICES DEPARTMENT.
- 2. THE CONTRACTOR IS RESPONSIBLE TO DETERMINE THE LOCATION OF ALL UTILITIES AND OTHER OBSTRUCTIONS ABOVE AND BELOW GROUND.
- 3. DURING THE TRANSPORTING, STORAGE AND PLANTING OF THE TREES THE CONTRACTOR WILL USE APPROPRIATE WORK PRACTICES TO NOT DAMAGE THE TREE, OR ROOT BALL. THE CONTRACTOR WILL ALSO ENSURE THAT THE TREE DOES NOT SUFFER DROUGHT STRESS DURING THIS OPERATION.
- 4. ALL TWINE AND BURLAP WILL BE BIO-DEGRADABLE. IF THE TREE HAS BEEN REBURLAPED THE OUTER BURLAP OUTSIDE OF THE WIRE BASKET WILL BE REMOVED.
- 5. TREES WILL BE PLANTED IN ACCORDANCE TO THE PLANTING DETAIL. THE DEPTH OF THE PLANTING HOLE WILL BE DETERMINED BY THE DEPTH OF THE ROOT BALL, ENSURING THAT THE TREES STRUCTURAL ROOTS ARE 2.5 TO 7.5 CM WITHIN THE FINISHED GRADE. SEE DETAIL 4
- 6. A 100 MM HIGH AND 150 MM WIDE SOIL RING WILL BE CREATED AT THE EDGE OF THE TREE HOLE. EXCESS SOIL WILL NOT BE ADDED TO THE ROOTBALL, ALL EXCESS SOIL WILL BE REMOVED FROM THE SITE.
- 7. 50 MM OF AN ORGANIC MULCH WILL BE APPLIED TO THE SURFACE OF THE SOIL RING AND ROOTBALL. THE MOUNDING OF SOIL AND MULCH WITHIN THE ROOTBALL AND AGAINST THE TREE TRUNK IS PROHIBITED.
- 8. THE TREE WILL BE WATERED IMMEDIATELY AFTER PLANTING AND THE PLACEMENT OF THE MULCH, WITH THE TREE SAUCER BEING COMPLETELY FILLED WITH WATER.
- 9. AN EXPANDABLE TREE COVER 200MM HIGH WILL BE PLACED AROUND THE BASE OF THE TREE.
- 10. TWO WOODEN STAKES 50MM X 50 MM X 2 M WILL BE PLACED OUTSIDE OF THE ROOT BALL AND FLEXIBLE TIES WILL BE USED.
- 11. TREES NOT PLANTED TO THIS SPECIFICATION, AND NOT AT THE APPROVED DEPTH, OR TREES THAT SETTLE AFTER PLANTING WILL BE REMOVED AND REPLANTED AT THE CONTRACTORS EXPENSE. IF THE TREE BALL CANNOT BE REMOVED FROM THE HOLE INTACT TO THE SATISFACTION OF CSD, THE TREE WILL BE REPLACED AT THE CONTRACTORS FULL EXPENSE.
- 12. TREE TO BE WATERED AND MULCHED IMMEDIATELY FOLLOWING PLANTING.
- 13. TREE SHALL BEAR SAME RELATION TO FINISHED GRADE AS IT BORE TO PREVIOUS EXISTING GRADE, FOLLOWING SETTLEMENT.

Plotted by: yvonnew Filename: S:\Secured\Design & Development\5 - AutoCAD Library\4 - Details\900 - Planting\UF.4.1 - STREET TREE-PLANTING.dwg

